



High Temperature Outlet Series



High Velocity Task / Air Outlet

- No Adhesives, Silicones or Felt Gasket
- Suitable for Labs, Clean Rooms, Air Showers, Spray Booths & Ovens
- Up to 500° F Operating Temperature

Adjustability

- Lock Down Adjustment
- Directional Air Pattern Control
70° Global Rotation Minimum
±35° Deflection
360° Rotation

MODEL	Size	A	B	D	F	H	Mtg Holes
HTO-03*	3	1-5/8	1-3/4	3-1/8	5	2-11/16	3
HTO-04	4	2	2-9/16	4	6	3-5/16	3
HTO-05	5	2-1/2	2-5/8	5	7	4	3
HTO-06	6	3	3-1/16	6	8	4-1/2	4
HTO-08	8	4-3/8	4-1/4	8	10	6	4
HTO-10	10	5-3/4	5-1/2	10	12	8-3/8	6
HTO-12	12	7-3/8	6	12	14	9	6

(Inches measured to the nearest 1/16")

Standard Finishes

- #00 mill
- #10 clear anodized

Material

- Heavy Gauge Aluminum

Notes

- Mounting Screws Included

Accessories

- Flex Duct Mounting Ring

Project :		<h2>HTO Series</h2> <p>High Temperature Outlet</p>
Architect :		
Engineer :		
Contractor :		Form # : 20043S
Submitted By :	Date :	Drawn By : MH January 2018